

SIVGE B40 SERIES

Mobile Elevating Work Platforms



Product conform with below standards:

- 2006/42/EC Machinery Directive
- EN 280-2013+A1-2015
- EN ISO 12100: 2010
- EN 60204-1:2006+A1:2009+AC:2010
- EN ISO 13849-1:2015
- GB25949-2010
- JB/T12216-2015

- * Suitable for 2 persons to work upraised.
- * Maximum working height available:
8m, 10m, 12m, 14m, 16m
- * Power supply available:
 1. Single phase AC220V/50Hz
 2. Uninterrupted Power Supply



HANGZHOU SIVGE MACHINERY CO.,LTD
ADD: NO 15 KANGXIAN ROAD, GONGSHU DISTRICT,
HANGZHOU, ZHEJIANG, CHINA
POST CODE: 310015 TEL: +86 571 88043728 88043711
FAX: +86 571 88043715 E-mail: info@sivge.com

© www.sivge.com
© www.aerial-workplatform.com
sivge stock(833084)

B40 Series Four Mast Mobile Elevating Work Platforms

STANDARD FEATURES:

- Dual controls operation
- Compact size with easy quick guardrail assemblage
- Emergency stop buttons at both controls
- Emergency lowering device in case of power supply failure
- 24V safe control voltage
- Double safety protection with leveling stabilizers and outriggers support
- Forklift pocket

	B4006	B4008	B4010	B4012	B4014
Model-code	GTWB6-4006	GTWB8-4008	GTWB10-4010	GTWB12-4012	GTWB14-4014
Platform height(m)(l_1)	6	8	10	12	14
Working height(m)(l_2)	8	10	12	14	16
Capacity(kg)/occupants	480/2	480/2	480/2	400/2	300/2
Platform size(mm)	1480*1000	1480*1000	1480*1000	1480*1000	1480*1000
Outrigger footprint(mm)	3350*3000	3350*2950	3350*2950	3350*2950	3350*2950
Stowed length(mm)(l_0)	2360	2360	2360	2360	2360
Stowed width(mm)(w_0)	1250	1250	1250	1250	1250
Stowed height(mm)(h_0)	1860	1860	2080	2460	2460
Machine weight(kg)	1300	1400	1500	1600	1800
Power supply	Elevating AC220V/1.5Kw; Driving DC24V/0.8Kw				
Front wheel	12 inch steering wheel				
Back wheel	12 inch driving wheel				
Wheelbase	1880mm				
Ground clearance	55mm				
Up-down speed	Up 4.6m/min; Down 5.5m/min.				
Moving methods	DC type walking control				
Steering mode	Wire control rear axle				
Travel speed (stowed)	1.4Km/h				
Travel speed (raised)	0				
Max. allowed wind speed	12.5m/s				
Rated oil pressure	12Mpa				
Battery	12V/120Ah*2				
Integrated charger	DC24V/15A with AC220V input				

Optional:

Platform extension	800mm,1000mm or according to request Specification will be changed if with extension platform function
Traveling method	Manual push around

- ※ Optional: design service is available if the standard models cannot fulfill the needs.
□ Product specifications are subject to change without notice or obligation.

